



- ❑ Stainless steel for cooking cabinet and exterior surface
- ❑ Oven capacity 1 x GN 2/1 or 2 x GN 1/1
- ❑ Oven temperature +50 ~ 250°C
- ❑ Separate regulating for upper and lower heating elements
- ❑ Manual valve for taking out the humidity from the cabinet inside

Subject to changes without notices (E.g. Model name,...)

JEITEK Corporation
845-2, BaekRok-Ri, HaBook-Myun,
Yang San-Si, Kyung Nam, Korea
Tel. +82 55 384 9400, fax +82 55 384 9471,
E-mail: jeitek@chollian.net



- ❑ Stainless steel for cooking cabinet and exterior surface
- ❑ Oven capacity 1 x GN 2/1 or 2 x GN 1/1
- ❑ Oven temperature +50 ~ 250°C
- ❑ Separate regulating for upper and lower heating elements
- ❑ Manual valve for taking out the humidity from the cabinet inside

Subject to changes without notices (E.g. Model name,...)

JEITEK Corporation
845-2, BaekRok-Ri, HaBook-Myun,
Yang San-Si, Kyung Nam, Korea
Tel. +82 55 384 9400, fax +82 55 384 9471,
E-mail: jeitek@chollian.net



- ❑ Stainless steel for cooking cabinet and exterior surface
- ❑ Oven capacity 1 x GN 2/1 or 2 x GN 1/1
- ❑ Oven temperature +50 ~ 250°C
- ❑ Separate regulating for upper and lower heating elements
- ❑ Manual valve for taking out the humidity from the cabinet inside

Subject to changes without notices (E.g. Model name,...)

JEITEK Corporation
845-2, BaekRok-Ri, HaBook-Myun,
Yang San-Si, Kyung Nam, Korea
Tel. +82 55 384 9400, fax +82 55 384 9471,
E-mail: jeitek@chollian.net



- Stainless steel for cooking cabinet and exterior surface
- Oven capacity 1 x GN 2/1 or 2 x GTN 1/1
- Oven temperature +50 ~ 250℃
- Separate regulating for upper and lower heating elements
- Manual valve for taking out the humidity from the cabinet inside
- Proving cabinet 3 x GN 2/1 or 6 x GN 1/1
- Proving temperature +30 ~ 110℃
- Two-door hinged type for proving cabinet

Subject to changes without notices (E.g. Model name,...)